

30. The composition of claim 29 where said lubricating composition consists essentially of a superabsorbent polymer combined with a material for decreasing friction between moving surfaces, where said superabsorbent polymer absorbs greater than about 100 times its weight in water and is a polymer of acrylic acid, an acrylic ester, acrylonitrile, acrylamide, co-polymers thereof or mixtures thereof, wherein said material for decreasing friction is a petroleum oil lubricant or grease thereof, and wherein said material for decreasing friction optionally contains a lubricant additive, wherein said lubricant additive is an antioxidant, rust inhibitor, antiwear compound, extreme pressure additive, detergent, dispersant, pour point depressant, viscosity-index improver, or foam inhibitor.

B Sub C2 31. The composition of claim 29 where said lubricating composition consists essentially of a superabsorbent polymer combined with a material for decreasing friction between moving surfaces, where said superabsorbent polymer absorbs greater than about 100 times its weight in water and is a polymer of acrylic acid, an acrylic ester, acrylonitrile, acrylamide, co-polymers thereof or mixtures thereof, wherein said material for decreasing friction is a solid lubricant, wherein said solid lubricant is an inorganic compound, carbon, or metal that provides barrier-layer lubrication, and wherein said material for decreasing friction optionally contains a lubricant additive, wherein said lubricant additive is an antioxidant, rust inhibitor, antiwear compound, extreme pressure additive, detergent, dispersant, pour point depressant, viscosity-index improver, or foam inhibitor.

00357957-072499
00357957-072499

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, D. C. 20005
202-408-4000

003577-019
657220-2562560

Sub E2

32. The composition of claim 31 where said solid organic lubricant is molybdenum disulfide, cobalt chloride, antimony oxide, niobium selenide, tungsten disulfide, mica, boron nitride, silver sulfate, cadmium chloride, cadmium iodide, borax, basic white lead, lead carbonate, lead iodide, asbestos, talc, zinc oxide, carbon, babbitt, bronze, brass, aluminum, gallium, indium, thallium, thorium, copper, silver, gold, mercury, lead, tin, indium, or the Group VIII noble metals or mixtures thereof.

B1

33. The composition of claim 29 where said lubricating composition consists essentially of a superabsorbent polymer combined with a material for decreasing friction between moving surfaces, where said superabsorbent polymer absorbs greater than about 100 times its weight in water and is a polymer of acrylic acid, an acrylic ester, acrylonitrile, acrylamide, co-polymers thereof or mixtures thereof, wherein said material for decreasing friction is a solid organic lubricant, and wherein said material for decreasing friction optionally contains a lubricant additive, wherein said lubricant additive is an antioxidant, rust inhibitor, antiwear compound, extreme pressure additive, detergent, dispersant, pour point depressant, viscosity-index improver, or foam inhibitor.

Sub C3

34. The composition of claim 33 where said solid organic lubricant is a fluoroalkylene homopolymer or copolymer, a lower alkylene polyolefin homopolymer or co-polymer, a paraffinic hydrocarbon, wax, phenanthrene, copper phthalocyanine, or mixtures thereof.

39. The composition of claim 29 where said lubricating composition consists essentially of a superabsorbent polymer combined with a material for decreasing friction between moving surfaces, where said superabsorbent polymer absorbs greater than about 100 times its weight in water and is a polymer of acrylic acid, an acrylic ester, acrylonitrile, acrylamide, co-polymers thereof or mixtures thereof, wherein said material for decreasing friction is a phosphate, and wherein said material for decreasing friction optionally contains a lubricant additive, wherein said lubricant additive is an antioxidant, rust inhibitor, antiwear compound, extreme pressure additive, detergent, dispersant, pour point depressant, viscosity-index improver, or foam inhibitor.

Sub C 5
BT
40. The composition of claim 38 where said material for decreasing friction is zinc phosphate, iron phosphate or manganese phosphate, or mixtures thereof.

41. The composition of claim 29 where said lubricating composition consists essentially of a superabsorbent polymer combined with a material for decreasing friction between moving surfaces, where said superabsorbent polymer absorbs greater than about 100 times its weight in water and is a polymer of acrylic acid, an acrylic ester, acrylonitrile, acrylamide, co-polymers thereof or mixtures thereof, wherein said material for decreasing friction is a fatty oil, fatty acid or wax, and wherein said material for decreasing friction optionally contains a lubricant additive, wherein said lubricant additive is an antioxidant, rust inhibitor, antiwear compound, extreme pressure additive, detergent, dispersant, pour point depressant, viscosity-index improver, or foam inhibitor.

Sub E 37

42. The composition of claim 29 where said lubricating composition consists essentially of a superabsorbent polymer combined with a material for decreasing friction between moving surfaces, where said superabsorbent polymer absorbs greater than about 100 times its weight in water and is a polymer of acrylic acid, an acrylic ester, acrylonitrile, acrylamide, co-polymers thereof or mixtures thereof, wherein said material for decreasing friction is a synthetic oil lubricant, or grease thereof, and wherein said material for decreasing friction optionally contains a lubricant additive, wherein said lubricant additive is an antioxidant, rust inhibitor, antiwear compound, extreme pressure additive, detergent, dispersant, pour point depressant, viscosity-index improver, or foam inhibitor.

567220 25525600

B1

43. The composition of claim 29 where said lubricating composition consists essentially of a superabsorbent polymer combined with a material for decreasing friction between moving surfaces, where said superabsorbent polymer absorbs greater than about 100 times its weight in water and is a polymer of acrylic acid, an acrylic ester, acrylonitrile, acrylamide, co-polymers thereof or mixtures thereof, wherein said material for decreasing friction is a soap, and wherein said material for decreasing friction optionally contains a lubricant additive, wherein said lubricant additive is an antioxidant, rust inhibitor, antiwear compound, extreme pressure additive, detergent, dispersant, pour point depressant, viscosity-index improver, or foam inhibitor.